

 Tesla, Inc. Service Bulletin		<h2>Replace Front Brake Rotors</h2>	
SB-26-33-002 February 25, 2026			
Classification Repair Bulletin		Section/Group 33 - Brakes	Mobile Service Can Perform (where permitted)
		Configuration Dual Motor	
Model Model Y	Model Year 2025–2026	Country/Region Europe, Middle East, Africa, Taiwan, Canada, Australia, New Zealand	Build Location Giga Berlin
<small>The model(s) and model year(s) listed are a general approximation of the affected VIN list. Refer to the VIN/Bulletin Tracker or Customer/Vehicle profile to determine applicability of this bulletin for a particular vehicle.</small>			

This repair bulletin provides instructions on addressing a possible customer concern regarding the operation of Tesla vehicles. These instructions should only be performed by trained professionals.

Condition

On certain model year 2025 and 2026 Model Y vehicles built at Giga Berlin, the front brakes may exhibit a squealing noise when braking in cold and/or humid conditions.

Correction

Upon customer complaint of a squealing noise coming from the front brakes during braking on a vehicle that has driven less than 50,000 km (31,070 miles), replace the front brake rotors with the updated part.

 **NOTE:** If this bulletin is applicable to the vehicle, perform the correction without any need for inspection.

Correction Description	Correction	Time
Replaced Front Brake Rotors and Burnished the Brakes	S012633002	0.84

	Part Number	Description	Quantity
Parts Required	1088969-00-B	BOLT,TE,M12-1.75x45,[109],G0110[B],SMAT	4
	For all countries except Canada		
	2188611-00-A	FRONT BRAKE ROTOR	2
	For Canada		
	1188611-00-A	FRONT BRAKE ROTOR	2
	These part numbers were current at the time of publication. Use the revisions listed or later, unless otherwise specified in the Parts Catalog .		
Special Tools	1082171-00-A	S-HOOK, BRAKE CALIPER (SET OF 2)	

Procedure

1. Replace the front brake rotors (refer to Service Manual procedure [3301011102](#)).
2. Burnish the brakes (refer to Service Manual procedure [33013000](#)).